

## Model BP2-G Temperature Sensor

### SPECIFICATION SHEET



- NIST certificates are available and recommended if storing vaccines
- 10' of wire included with each sensor, more available for purchase
- Vials filled with propylene glycol are designed to mimic a vaccine bottle
- For models VM605E, VM505E, VM505 M303, CM712, M305, MA412

#### Description:

The temperature sensors incorporate a Class A, Thin Film Platinum RTD sensor which conforms to DIN-IEC-751 platinum RTD standards. These sensors are available in two or three wire configurations, incorporating high accuracy and interchangeability throughout a wide operating temperature range.

These sensors are offered in Room (R)\*, BP (bullet probe) BP-V (bullet probe in a vial with glass beads), BP2-G (2" sensor in glycol filled vial) and Stainless Plate (SP)\*

BP2-G vial is approximately 1.25" wide and 2.75" tall and holds 1 oz. of liquid.

### Specifications

Output	1K Ohms @ 32°F (0°C)
Accuracy	+/- 0.06% @ 32°F (0°C) Single Point +/- 1.0 Ohm @ 70°F (Averaging)
Stability	Less than +/- 0.1°C drift
Repeatability	+/- 0.2°C (+/- 0.36°F)
Operating Temp. Range	BP -58 to 392°F (-50 to 200°C) BP-V
Temperature Coefficient	0.00385 Ohm/Ohm/°C
Standardization	DIN-IEC-751 (formerly DIN 43760)
Resistance Characteristics	+/- 0.06% Class A (Standard)